

Poly(ethyl vinyl ether) Resin - LUTA-25

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Poly(ethyl vinyl ether) Resin - LUTA-25
CAS Number: 25104-37-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use: Laboratory research use only

1.3 Details of the supplier of the safety data sheet

Company name: East Harbour Group Ltd
20 Clough Road, Severalls Industrial Park
Colchester, Essex, CO4 9QS
United Kingdom

Telephone: +44 (0) 333 242 0100
Email: info@eastharbourgroup.com

1.4 Emergency telephone number

Emergency telephone: 0800 246 1274

Section 2: Hazardous identification

2.1 Classification of the substance or mixture

OSHA Haz Com: CFR 1910.1200

Acute Toxicity - Oral [Category 4]
Skin Corrosion/Irritation [Category 2]
Eye Damage/Irritation [Category 2A]

2.2 Label elements

Pictogram



Signal Word

Warning

Hazard Statement(s)

Causes serious eye irritation.
Causes skin irritation.
Harmful if swallowed.

Precautionary Statement(s):**[Prevention]**

Do not eat, drink or smoke when using this product. Wash hands and face thoroughly after handling. Wear protective gloves. Wear eye and face protection.



Poly(ethyl vinyl ether) Resin - LUTA-25

[Response]

If swallowed: Immediately call a poison center or doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

[Storage]

None

[Disposal]

Dispose of contents and container in accordance with US EPA guidelines for the classification and determination of hazardous waste listed in 40 CFR 261.3. (See Section 13)

Section 3: Composition/information on ingredients

Substance/Mixture Components	Substance Poly(ethyl vinyl ether) Resin - LUTA-25
Percent	> 90.0%
CAS Number	25104-37-4
Molecular Weight	N/A
Chemical Formula	N/A

Section 4: First aid measures

4.1 Description of first aid measures

Inhalation

Call a poison center or doctor if you feel unwell. Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Keep victim warm and quiet. Treat symptomatically and supportively. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Skin contact

Call a poison center or doctor if you feel unwell. Remove and wash contaminated clothing before re-use. Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Treat symptomatically and supportively. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Eye contact

IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Contact with material may irritate or burn eyes. Call emergency medical service. Move victim to fresh air. Check for and remove any contact lenses. Keep victim warm and quiet. Treat symptomatically and supportively. Effects of exposure to substance may be delayed. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Ingestion

Harmful if swallowed. Do not induce vomiting without medical advice. If swallowed, seek medical advice immediately and show the container or label. Do not use mouth-to-mouth method if victim ingested the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Loosen tight clothing such as a collar, tie, belt or waistband. If a person



Poly(ethyl vinyl ether) Resin - LUTA-25

vomits place them in the recovery position so that vomit will not re-enter the mouth and throat. Rinse mouth. Keep victim warm and quiet. Treat symptomatically and supportively. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Symptoms/effects

Acute

Redness.

Delayed

No data available.

Immediate medical attention

WARNING: It might be hazardous to the person providing aid to give mouth-to-mouth respiration, because the inhaled material is harmful. If breathing has stopped, perform artificial respiration. Use first aid treatment according to the nature of the injury. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Section 5: Fire-fighting measures

5.1 Fire Fighting Media and Instructions:

Suitable extinguishing media

Dry chemical, CO₂, sand, earth, water spray or regular foam Consult with local fire authorities before attempting large scale firefighting operations.

Specific hazards arising from the chemical

Hazardous combustion products

These products include: Carbon oxides Nitrogen oxides Sulfur oxides Halogenated compounds

Other specific hazards:

WARNING Highly toxic HCl gas is produced during combustion.

Special precautions for fire-fighters

Use water spray or fog; do not use straight streams. Dike fire-control water for later disposal; do not scatter the material. Containers may explode when heated. Move containers from fire area if you can do it without risk.

Special protective equipment for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural fire fighters' protective clothing provides limited protection in fire situations ONLY; it may not be effective in spill situations. Wear chemical protective clothing which is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes, and clothing. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing (Section 8). Warn unnecessary personnel to move away. Stop leak if you can do it without risk. Ensure adequate ventilation. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Personal protective equipment



Poly(ethyl vinyl ether) Resin - LUTA-25

Wear eye protection (splash goggles) and face protection (full length face shield). Lab coat. Dust respirator. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Wear protective gloves (nitrile)

Emergency procedures

Prevent dust cloud. In case of a spill and/or a leak, always shut off any sources of ignition, ventilate the area, and exercise caution. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Warn personnel to move away. Prevent entry into sewers, basements or confined areas; dike if needed.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if without risk. Ventilate the area. Absorb with an inert material and put the spilled material in an appropriate waste disposal container. Use clean non-sparking tools to collect absorbed material.

Environmental precautions

Keep away from living quarters. Prevent further leakage or spillage if safe to do so. Water runoff can cause environmental damage. Prevent entry into sewers, basements or confined areas; dike if needed.

Section 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling

Avoid inhalation of vapor or mist. Do not ingest. Avoid contact with skin and eyes. Good general ventilation should be sufficient to control airborne levels. Keep container dry. Handle and open container with care. Wear suitable protective clothing, gloves and eye/face protection. When using do not eat, drink, or smoke. Keep away from sources of ignition.

Conditions for safe storage

Keep only in the original container in a cool well-ventilated place. Keep away from incompatibles. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Avoid prolonged storage periods. Store under inert gas (e.g. Argon). Hygroscopic material, store in a tightly sealed container. Store in refrigerator.

Storage incompatibilities

Store away from oxidizing agents.

Section 8: Exposure controls/personal protection

8.1 Control parameters

Exposure limits

No data available

Appropriate engineering controls

Good general ventilation should be sufficient to control airborne levels. Ventilation is normally required when handling or using this product. Eyewash fountains should be provided in areas where there is any possibility that workers could be exposed to the substance. Follow safe industrial engineering/laboratory practices when handling any chemical.

Personal protective equipment

Respiratory protection



Poly(ethyl vinyl ether) Resin - LUTA-25

Dust respirator. Be sure to use a MSHA/NIOSH approved respirator or equivalent.

Hand protection

Nitrile gloves.

Eye protection

Safety glasses.

Skin and body protection

Lab coat.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Colorless to light yellow viscous transparent liquid
Melting point	No data available
Boiling point	No data available
Flash point	> 55
Relative density	~0.96g/cm ³ @20°C
Kinematic Viscosity	2,500-6,000@23°C, mPa·s
Partition coefficient	No data available
Flammability (solid, gas)	No data available

Section 10: Stability and Reactivity

Reactivity	No data available
Chemical Stability	No data available
Possibility of Hazardous Reactions	No data available
Conditions to avoid	No data available
Incompatible materials	No data available
Hazardous Decomposition Products	No data available

Section 11: Toxicological Information

Acute Toxicity

No data available

Skin corrosion / irritation

No data available

Serious eye damage / irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available



Poly(ethyl vinyl ether) Resin - LUTA-25

Carcinogenicity
No data available

IARC
No data available

NTP
No data available

OSHA
No data available

Reproductive toxicity
No data available

Routes of Exposure
Inhalation, Eye contact, Ingestion, Skin contact.

Symptoms related to exposure
Overexposure may result in serious illness or death. Skin contact may result in inflammation; characterized by itching, scaling, reddening, or occasionally blistering. Skin contact may result in redness, pain or dry skin. Eye contact may result in redness or pain.

Potential Health Effects
Skin and eye contact may result in irritation.

Target organ(s)
No data available

Section 12: Ecological Information

12.1 Toxicity
Ecotoxicity
Fish
No data available

Crustacea
No data available

Algae
No data available

Persistence and degradability
No data available

Bioaccumulative potential (BCF)
No data available

Mobility in soil
No data available



Poly(ethyl vinyl ether) Resin - LUTA-25

Partition coefficient n-octanol/water (log Pow)

No data available

Soil adsorption (Koc)

No data available

Henry's Law constant (PaM³/mol)

No data available

Section 13: Disposal considerations

13.1 Waste treatment methods

Disposal of product

Recycle to process if possible. It is the generator's responsibility to comply with Federal, State and Local rules and regulations. You may be able to dissolve or mix material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber system. This section is intended to provide assistance but does not replace these laws, nor does compliance in accordance with this section ensure regulatory compliance according to the law. US EPA guidelines for Identification and Listing of Hazardous Waste are listed in 40 CFR Parts 261. The product should not be allowed to enter the environment, drains, water ways, or the soil.

Disposal of container

Dispose of as unused product. Do not re-use empty containers.

Other considerations

Observe all federal, state and local regulations when disposing of the substance.

Section 14: Transport Information

DOT (US)	Non-hazardous for transportation.
IATA	Non-hazardous for transportation.
IMDG	Non-hazardous for transportation.

Section 15: Regulatory Information

Toxic Substance Control Act (TSCA 8b.)

This product is ON the EPA Toxic Substances Control Act (TSCA) inventory.

US Federal Regulations

CERCLA Hazardous substance and Reportable Quantity

SARA 313	Not Listed
SARA 302	Not Listed

State Regulations

State Right-to-Know

Massachusetts	Not Listed
New Jersey	Listed
Pennsylvania	Not Listed
California Proposition 65	Not Listed



Poly(ethyl vinyl ether) Resin - LUTA-25

Other Information

NFPA Rating

Health	1
Flammability	2
Physical	0

HMIS Classification

Health	1
Flammability	2
Instability	0

